



◎DP-5201A (+/- 1300V / 35MHz) Differential Probe

Features :MAX. Input Voltage: +/-1300V (DC + AC peak)Bandwidth: 35MHz all rangesAttenuation...



◎DP-5203A (+/- 1300V / 70MHz) Differential Probe

Features :MAX. Input Voltage: +/-1300V (DC + AC peak)Bandwidth: 70MHz all rangesAttenuation...



◎DP-5205A (+/- 1300V / 100MHz) Differential Probe

Features :MAX. Input Voltage: +/-1300V (DC + AC peak)Bandwidth: 100MHz x 500, 90MHz x...



◎DP-5403HS (100V p-p/70MHz) Differential Probe

Features :1:1 Model, Attenuation: X1 or X10High Frequency Operation70 MHz All RangeInput...



◎DP-5609UF (520V p-p/200MHz) Differential Probe

Features :200MHz Bandwidth (All Range)Rise Time: 1.75 nS5MHz Limit Bandwidth...

DP-5000series 差動型プローブ (新モデル)

WEB-PAGE ▶ [DP-5200差動プローブ](#)

▶ [DP-5403HS差動プローブ](#)

▶ [DP-5609UF差動プローブ](#)

PINTEK High Sensitivity Differential Probe
High sensitivity model DC~70MHz(1:1, -3dB)
★ High Sensitivity Model!

DP-5403HS

Features:

- 1:1 Model,
- Attenuation: X1 or X10
- High Frequency Operation 70 MHz Full Range
- Input Impedance:
X1: 1 MΩ / 6 PF
X10: 1 MΩ / 1 PF
- Especially for Low Voltage:
X1: ± 5 V DC or 10 V p-p
X10: ± 50 V DC or 100 V p-p

CE

Pintek Electronics Co., Ltd
www.pintek.com.tw

